STATE OF IZ-06
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C. HIGHWAY PAVEMENT MARKING (USDOT-FHWA) STANDARD ALPHABET AND SYMBOLS FOR

**PAVEMENT MARKINGS** 

**ENGLISH** STANDARD DRAWING FOR

## **GENERAL NOTES:**

- 1- STANDARD CHARACTERS ARE 25 GRID UNITS HIGH AND 4 UNITS WIDE (EXCEPT LETTER "I" AND THE NUMBER "1" WHICH ARE 1 UNIT WIDE).
- 2- VERTICAL STROKES ARE 1 UNIT WIDE, HORIZONTAL STROKES ARE 4 UNITS HIGH.
- 3- SPACE 1 UNIT (MIN.) BETWEEN CHARACTERS OR AS OTHERWISE SHOWN (OPTICAL SPACING MAY BE USED).
- 4- STANDARD CHARACTER HEIGHTS ARE 8'-4". EXCEPT FOR THE 6' RAILROAD 'R' SYMBOL AND THE TWO-LANE 10'-5" SCHOOL SYMBOL.

- 5- FOR 8'-4" HIGH CHARACTERS, THE WIDTH IS 16" (USE 4" FOR EACH GRID SQUARE).
- 6- FOR 10'-5" HIGH CHARACTERS, THE WIDTH IS 20" (USE 5" FOR EACH GRID SQUARE).
- 7- FOR 6' HIGH CHARACTERS, THE WIDTH IS 111/2" (USE 27/8" FOR EACH GRID SQUARE).

FOR FOR SYMBOLS MARKINGS AND **ALPHABET PAVEMENT** ENGLISH STANDARD

DRAWING

STANDARD

HIGHWAY PAVEMENT MARKING (USDOT-FHWA)

NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C.

STATE NORTH CA

SHEET 7 OF 7 1205.08

SHEET 7 OF 7 1205.08